

应用领域

- 用户侧C&I工商业储能的峰谷套利,后备电源;
- 风光新能源电站的削峰填谷平滑输出;
- 电网侧调频调峰,配电网变压器容量扩容



全舱温差
<3°C



PACK级消防
高安全性



高能量密度
灵活布置及扩容



模块化预制
无需现场安装

参数/型号		EnerGalactic-5015-0.5C
电池模块	电芯容量	314Ah
	模块成组	1P52S
	模块标称电压	166.4V
	模块能量	52.2496kWh
	防护等级	IP67
电池簇	模块数量	8pcs
	电池簇标称电压	1331.2V
	电压范围	1164.8~1476.8V
	单簇能量	417.997kWh
电池舱	电池簇数量	12pcs
	电池系统电量	5015kWh
	电池舱尺寸 (W*D*H)	6058*2438*2896mm
	重量	≤43t
	冷却方式	液冷
	防护等级	IP54
符合标准	Cluster	IEC62619、UL1973、UL9540A、UN38.3



昆宇电源股份有限公司

网址:WWW.COSPOWERS.COM

地址:山东省东营市东营区东七路28号

电话:0546-7768891

版权及最终解释权归昆宇电源股份有限公司所有

Application Field

- Post-meter electricity market, peak-valley arbitrage and backup power supply of C&I (commercial and industrial) energy storage on the customer side.
- Peak shaving and valley filling for smooth output of wind and solar new energy power stations.
- Grid frequency regulation and peak load regulation in the pre-meter electricity market, as well as capacity expansion of distribution network transformers.



Temperature Difference
inside the Battery
Pack: <3°C



High Safety Fire
Protection at the
Pack Level



High Energy Density
for Flexible Layout
and Expansion



Modular Prefabrication
No On-site Installation
Required

Parameters/ Model		EnerGalactic-5015-0.5C
Battery module	Cell Capacity	314Ah
	Battery Pack	1P52S
	Module Voltage	166.4V
	Module Power	52.2496kWh
	IP Class	IP67
Battery cluster	Nos.of Modules	8pcs
	Cluster Nominal Voltage	1331.2V
	Voltage Range	1164.8~1476.8V
	Single Cluster Power	417.997kWh
Battery cabin	Nos. of Battery Clusters	12pcs
	Battery system energy	5015kWh
	Battery Cabin Dimension (W*D*H)	6058*2438*2896mm
	Weight	≤43t
	Cooling Method	Liquid cooling
	IP Class	IP54
Compliant with Standards	Cluster	IEC62619, UL1973, UL9540A, UN38.3



Cospowers Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T:+86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.